

Vivo

 climatex®



Vivo

 climatex®



471 150-605



471 150-603



471 150-823



471 150-829



471 150-102



471 150-822




471 150-110



471 150-190



471 150-107




471 150-108



471 150-109

Vivo

 climatex®




471 150-210



471 150-302



471 150-332



471 150-333



471 150-335




471 150-827



471 150-705



471 150-809



471 150-502



471 150-856

Vivo


 climatex®




471 150-505




471 150-510




471 150-907




471 150-555



471 150-905



471 150-985



471 150-901



471 150-999

Vivo

 climatex®

Design

Climatex

Farben – Colors – Colori – Couleur

29

Material – Composition – Composizione – Composition

60 % Certified Virgin Wool, WV

40 % Redesigned Lenzing FR™, CV FR

Nutzbreite – Nominal Width – Larghezza utilizzabile – Largeur utile

138 cm

Gewicht – Weight – Peso – Poids

485 g/lfm

Schallabsorption – Sound absorption – Assorbimento acustico – Absorption acoustique

$\alpha_w = 0,55$

Scheuerfestigkeit – Abrasion resistance – Resistenza all'abrasione – Résistance à l'abrasion

40'000 Martindale, EN ISO 12947-2

Pilling – Résistance au boulochage

4 - 5, EN ISO 12945-2

Lichtechtheit – Light fastness – Solidità alla luce – Stabilité aux UV

5, EN ISO 105-B02

Reibechtheit – Fastness to rubbing – Resistenza allo sfregamento – Résistance au frottement

dry 4, wet 4, EN ISO 105-X12

Brandnormen – Fire standards – Norme antincendio – Normes incendie

EN 1021-1/2

BS 5852-0/1

EN 11925-2, E

ÖNORM B 3825, B1

California TB 117, Class 1

FAR/JAR 25.853

Pflege – Care – Cura – Conseil d'entretien

